

**Druckgewindeformer      Tarauds à refouler      Thread former      582985..**

Gewindefomer in HSS-E für höchste Ansprüche, spanlos arbeitend, Gewinde gefräst, 4-Kant Profil, Standard Toleranz 6H, lieferbar auch in 4H, 5H, 5G, 6G  
 Hauptanwendung:  
 Edelstahl, weiches Messing, Messing Ms61, Kupfer, Silber, Aluminium, Gold usw.


Tarauds de hautes performances en HSS-E travaillant sans enlèvement de copeaux, fillet fraisé, profile carré. Tolérance standard: 6H; 4H, 5H, 5G, 6G sur demande.  
 Application principale:  
 acier inoxydables, laiton tendre ,laiton Ms61, cuivre, argent, aluminium, or etc.

High quality performance thread former in HSS-E for highest requirements chipless working, milled thread, square profile, standard tolerance 6H, available also in tolerances 4H, 5H, 5G, 6G  
 Main application:  
 Stainless steels, soft brass, brass Ms61, copper, silver, aluminium, gold etc.

**Minimalbestellmenge:** 10 Stück pro Abmessung  
**Volumenrabatt:** auf Anfrage Beschichtungen in TiALN, Xtreme uam.auf Anfrage

**Commande minimale:** 10 pcs. par dimension  
**Rabais de quantité:** sur demande. Revêtement: en TiALN, Xtreme et autres sur demande

**minimal order volume.** 10 pieces per dimension  
**Volume discount:** on request Coating in TiALN, Xtreme etc.on request



Gewinde Filet thread	Steigung pas pitch	aussen extérieur outside	Schaft tige shaft	Gesamtlänge longueur tot. total length	Schnittlänge long. de coupe cutting length	Kernloch perçage core hole	582985.. Best. Nr. no.cde. order no.	5.82985114 CHF
Ø	p	Ø	Ø	l1	l2	Ø		
M 0,40 x 0,10	0,435	1,50	25	2	0,35	582985. 040	15,80	
M 0,50 x 0,13	0,535	1,50	25	2,5	0,44	582985. 050	11,70	
M 0,60 x 0,15	0,635	1,50	25	3	0,53	582985. 060	11,70	
M 0,70 x 0,18	0,745	1,50	25	4	0,62	582985. 070	8,20	
M 0,80 x 0,20	0,845	1,50	25	4	0,70	582985. 080	8,20	
M 0,90 x 0,225	0,945	1,50	25	4	0,80	582985. 090	8,20	
M 1,00 x 0,25	1,045	1,50	25	5	0,90	582985. 100	8,20	
M 1,10 x 0,25	1,145	1,50	25	5	1,00	582985. 110	8,20	
M 1,20 x 0,25	1,245	1,50	25	5	1,10	582985. 120	8,20	
M 1,30 x 0,30	1,345	1,50	25	6	1,15	582985. 130	8,20	
M 1,40 x 0,30	1,445	1,50	30	6	1,25	582985. 140	8,80	
M 1,50 x 0,30	1,545	1,50	30	6	1,35	582985. 150	8,80	
M 1,60 x 0,35	1,645	1,50	30	8	1,45	582985. 160	8,80	
M 1,70 x 0,35	1,745	1,50	30	8	1,55	582985. 170	8,80	
M 1,80 x 0,25	1,845	1,50	30	8	1,65	582985. 180	8,80	
M 2,00 x 0,40	2,080	1,50	35	10	1,80	582985. 200	9,40	
M 2,20 x 0,45	2,280	1,50	35	10	2,00	582985. 220	9,40	
M 2,30 x 0,40	2,380	1,50	35	10	2,10	582985. 230	9,40	
M 2,50 x 0,45	2,580	1,50	35	10	2,30	582985. 250	9,40	
M 2,60 x 0,45	2,680	1,50	35	10	2,40	582985. 260	9,40	
M 3,00 x 0,50	3,080	1,50	40	12	2,75	582985. 300	10,50	

Andere Dimensionen auf Anfrage/autres dimensions sur demande/other dimensions on request